



# EU Declaration of Conformity

- Reference No. : N8 14 09 54505 061(TUV\_SUD)
- Manufacturer : Kun Hung Electric Co., Ltd.  
183, Hancheon-ro, Dongdaemun-gu, Seoul, 02534 Rep. of Korea
- Product : MICRO SWITCH
- Model(s) : KH-9015 Series
- Rated input voltage : 250V a.c
- Rated input current : 10A
- Rated insulation voltage : 500V a.c
- Rated impulse withstand Voltage : 1.5kV
- Utilization category : AC-15(Resistive)
- Degree of protection : IP 50
- Pollution degree : 3
- Overvoltage category : III
- Number of operating cycles : 500000(electrical)  
10000000(mechanical)
- Harmonized Standard(s) : 2014/35/EU : EN 60947-1:2014  
Low-voltage switchgear and controlgear - Part 1: General rules  
EN 60947-5-1: 2016  
Low-voltage switchgear and controlgear - Part 5-1: Control circuit devices and switching elements - Electromechanical control circuit devices



We declare that the above products comply with the appropriate basic safety and health requirements of the EU Low Voltage Directive **2014/35 / EU** according to our design and type according to our distribution method. This declaration is invalid if the equipment is changed without our consent. This declaration of conformity is issued under the sole responsibility of the manufacturer.

Signature: Nov 09, 2020

S. H., Moon / Technical Director

## ■ ATTACHMENT 1

A. General product information:

### **KH-9015-w**

Remark:

w. Type of lever

- PBF: slim spring plunger,
- PBL: panel mount plunger,
- RP: panel mount roller plunger,
- CRP: panel mounts cross roller plunger,
- PBS: short spring plunger,
- HL: short hinge lever,
- HLL: long hinge lever,
- HP: leaf spring,
- HRL: long hinge roller lever,
- HRM: medium hinge roller lever,
- HRS: short hinge roller lever,
- HLZ: hinge lever Z type,
- HR(S)W: hinge roller lever W type